

PVDF Tubing

PVDF tubing enjoys inherent high purity, has smooth internal surfaces and exhibits very low fluid permeation through its wall making it ideal for the transport of ultra-pure fluids in the pharmaceutical and semi-conductor industries.

PVDF tubing is used widely in pure water systems thanks to PVDF containing no additives or damaging metal ion 'extractables' but such tubing is also used in municipal water treatment where its resistance to strong disinfecting solutions is an advantage.



PVDF tubing availability

- Long continuous lengths on spools or in coils
- Straight cut 'sticks'
- Ready assembled with connectors
- Thermoformed into 2D shapes
- Bagged directly off extruder to maintain cleanliness

Key features

- Temperature range from -40°C (-40°F) to 140°C (284°F)
- Chemically inert to most acids & chlorinated solvents
- Extremely hard, 78° shore D
- Excellent abrasion resistance
- Very smooth internal surfaces
- UL 94 V-O flammability rating
- Inherent high purity
- Physiologically harmless
- FDA conforming & USP Class VI compliant
- Gamma, EtO & autoclave (121°C / 250°F) sterilisable
- Well suited to high pressure applications
- Excellent weathering & exceptional UV stability



Standard metric sizes

ID	ID tol. +/-	OD	OD tol. +/-	W	W/P @ 23°C (bar)	B/P @ 23°C (bar)
1.00	0.10	2.00	0.10	0.50	44	220
2.00	0.10	4.00	0.10	1.00	44	220
2.50	0.10	4.00	0.10	0.75	26	132
3.00	0.10	4.00	0.10	0.50	14	73
4.00	0.10	6.00	0.10	1.00	22	110
5.00	0.15	8.00	0.15	1.50	26	132
6.00	0.10	8.00	0.10	1.00	14	73
8.00	0.10	10.00	0.10	1.00	11	55
9.00	0.15	12.00	0.15	1.50	14	73
10.00	0.15	12.00	0.15	1.00	9	44

W/P = Working Pressure | B/P = Burst Pressure

Standard imperial sizes

ID	ID (mm)	ID tol. +/- (mm)	OD	OD (mm)	OD tol. +/- (mm)	W (mm)	W/P @ 23°C (bar)	B/P @ 23°C (bar)
1/32"	0.79	0.10	1/16"	1.59	0.10	0.40	44	222
1/16"	1.59	0.10	1/8"	3.18	0.10	0.79	43	218
1/8"	3.18	0.15	1/4"	6.35	0.15	1.59	44	222
5/32"	3.97	0.15	1/4"	6.35	0.15	1.19	26	131
3/16"	4.76	0.10	1/4"	6.35	0.10	0.79	14	73
1/4"	6.35	0.15	3/8"	9.53	0.15	1.59	22	110
3/8"	9.53	0.20	1/2"	12.70	0.20	1.59	14	73
1/2"	12.70	0.20	5/8"	15.88	0.20	1.59	11	55
5/8"	15.88	0.25	3/4"	19.05	0.25	1.59	8	44
7/8"	22.22	0.30	1"	25.40	0.30	1.59	6	31

W/P = Working Pressure | B/P = Burst Pressure

Although the size range above satisfies most applications, many more sizes and custom dimensions are possible to suit your specific needs.

+44 (0)1785 859 054 enquiries@polyflon.co.uk www.polyflon.co.uk

16 Raleigh Hall, Eccleshall, Stafford, ST21 6JL

